



Mitsubishi FUSO New Zealand



UNPRECEDENTED STYLING AND COMFORT

The Rosa is a 24-passenger unit suitable for a wide range of applications from around-town route work to tourist operations and camper conversion.

Rosa has already established a solid reputation in New Zealand and this new model builds on that. It's a bus designed with driver operation in mind, made even easier by the six-speed automatic transmission as standard.

Going down those roads is made safe with the application of an exhaust brake, front disc and rear drum brakes and independent front suspension. ABS brakes are standard to assist vehicle control and driveability in braking situations.

Rosa is unique in the New Zealand market. It is competitively priced, delivers a comfortable quiet ride, meets the latest New Zealand emission standards and is backed by a national sales, parts and service network.



KEY FEATURES

6 spd AISIN automatic transmission

4M50, 5.0 Litre, 4-cylinder turbo diesel engine

7.5 metre turning radius

NZ new - factory warranty, parts and service backing.

ABS brakes

COMFORT FOR YOU AND YOUR PASSENGERS





Cockpit







Easy to use passenger entry and exit



Passenger seats

High performance ventilation system



Non-reflective meter cluster


CRUISING AND SAFETY



6 spd AISIN automatic transmission




4M50-3AT7, 5.0L, 4-cylinder turbo diesel engine



Turning radius



Independent front suspension



ABS brakes



GENERAL

BE64DJRMUFBD

ENGINE SPECIFICATIONS

Model:	Mitsubishi FUSO 4M50-3AT7
Туре:	4-stroke cycle, water cooled direct injection diesel engine
Number of Cylinders:	4 in line
Bore and Stroke	114 x 120mm
Piston Displacement:	4899cc
Max Output (ECE):	110kW/2700rpm
Max Torque (ECE):	470Nm/1600rpm
Exhaust Emission:	EPA 04
Generator:	24v, AC 80 amp
Fuel Inj Pump:	Electronic control
Air Cleaner:	Dry type with paper element
Turbo Charger:	With intercooler
Engine Equipment: plu	Power steering, heater, glow g, tachometer, exhaust brake

MASS

Empty Vehicle Mass:		4080kg
Max Gross Vehicle Mass:		6285kg
Maximum Permissible Vehicle Mass:	Front	2600kg
	Rear	3800kg

TOWING CAPACITY

Trailer Brake – with or without	:	715kg
DIMENSIONS		••
Wheel Base:		4550mm
Overall Length:		7730mm
Overall Height, Approx:		2630mm
Overall Width, Approx:		2070mm
Tread:	Front	1655mm
	Rear	1495mm
Body Inside:	Length	6970mm
	Width	1845mm
	Height	1860mm

PERFORMANCE (CALCULATED)

Max Speed (with speed limiter):	100km/h
Gradeability, Computed with GVM=6,285kg:	45%
Min Turning Radius:	7.2m

MISCELLANEOUS

Following equipment is provided:

- 1. Front & rear heater & defroster
- 2. Cigarette lighter
- 3. Reverse warning buzzer
- 4. Emergency hammer on the pillar to brake side window
- 5. Fire extinguisher attachment hole (225 x 40mm) on engine lid
- 6. Parcel racks
- 7. Digital clock

TRANSMISSION

Model:	Automatic, MO36A6, AISIN
Туре:	6 forward and 1 reverse speed
Ratio:	3.742-2.003-1.343-1.000-0.773-0.634,
	Rev. 3.539

FRONT AXLE

```
Independent Suspension Type
```

REAR AXLE

Full Floating Type:	
Final Reduction:	Single reduction, hypoid gear
Model:	D033H
Ratio:	5.285

TYRES & WHEELS

Single Front, Dual Rear

Tyre Size (wheel size all):	205/85R16-117/115
	(16x5.5: Silver)
	Yokohama RY208

STEERING

Right hand steering. Rack & pinion type with integral type hydraulic power booster. Tilt steering column

SUSPENSION

Front:	Double wishbone type independent suspension with shock absorbers
(Coil spring and transverse leaf spring (FRP)
Rear:	Long tapered leaf springs with shock absorbers and stabiliser
BRAK	ES 🔶
Service:	Hydraulic with vacuum servo assistance divided line with 9 + 10 inch size master vac
Front Br	ake: Disc brake with twin caliper, auto-adjuster
Rotor dia x rotor thickness x pad thicknes	
	235 x 40 x 14mm
Rear Bra	ake: Drum brake with auto-adjuster Drum dia x lining width x lining thickness 320 x 110 x 10mm
Parking:	Internal expanding type at rear side of transmission
Auxiliary	r: Exhaust brake
Anti-lock Brake System (ABS)	
FRAM	E 🔶

Туре:	Parallel tapered channel section type with cross-members
Material:	Hot rolled steel

COOLING SYSTEM

Radiator: Corrugated fin type & water reservoir

ELECTRICAL SYSTEM

24 Volt	
Batteries:	2 x 12v, 75D26R 52Ah at 5hr rate

FUEL TANK


2 E

100 litres with roll-over checked-value

WATER SEPARATOR	••
Primary fuel filter in fuel line	
Protector:	With



ROSA-BE64DJRMUFBD – SPECIFICATION DRAWING





BODY SPECIFICATIONS

ROSA MODEL CODE

BE64DJRMUFBD

MISCELLANEOUS

Following equipment is provided:

- 1. Standard tool set including hydraulic jack
- 2. Spare tyre and wheel
- 3. Engine warm-up switch and system

TYPE

Semi-integral (monocoque) type

BODY STRUCTURE

Pressed steel girder construction of pillars with spot welded outside panels and roof panels

INTERIOR FINISH

Ceiling Fron	t/Rear: Formed resin plates covered with vinyl leather
Centre:	Polypropylene honeycomb board covered with vinyl leather
Side Walls:	Moulded plastic plate covered with vinyl leather
Flooring:	Waterproof type plywood 12mm thick
Floor Cover:	Lino 1.6mm thick bonded to floor Colour: brown

WINDOWS

Front Safety:	Upper tinted and laminated heat absorbing green glass
Side:	Sash and sliding type Sash colour: black Heat absorbing dark-grey glass
Rear:	Heat absorbing green glass
Emergency Side W	Jindows: 2 emergency windows provided on the right side and 1 emergency window provided on the left side

SEATS

Seating Capacity:	24 passengers and 1 crew
Seating Arrangeme	nt: See drawing
Passengers' Seats:	High back, covered with cloth Armrests, cup holders and seat back pocket
Driver's Seat: Lo	w back and reclining seat with headrest, covered with cloth Seat sliding, seat back angle and height are adjustable
Seat Belt:	Assistant: ELR 3 point type Driver: ELR 3 point type Passenger: 2 point type

INTERIOR EQUIPMENT

Trim:	All pillars are fully covered with trim
Room Mirror:	196 x 86mm. 1 interior rear view mirror on the top of front windscreen
Sunvisor:	Pair of sunvisors for driver and assistant seats
Ashtray for Dr	iver: Provided
Door Pocket:	Provided on the driver's door

EXTERIOR EQUIPMENT

Bumpers, Front and Rear	Pressed steel, painted bumpers
Licence Number Plate:	1 on front bumper and 1 rear bumper
Front Grille:	Mesh type. Colour: black
Rear View Mirrors:	Plane mirror provided
Front Under View Mirror:	Round type sub mirror, on the left side
Rear Under View Mirror:	Attached to rear door upper
Safety Mirror For Entrance	e: Provided
Splash Guard: P	rovided, behind each tyre
Spare Tyre Carrier:	Wind-up type, under the rear overhang
Towing Hooks:	1 hook at front frame

ELECTRICAL EQUIPMENT

Radio:	AM/FM radio with 4 speakers and CD player
Microphone:	Provided
Horn:	Single electric
Windscreen Wipers and Washers	Dual blades, 3 speed wipers 2.5 litre water tank

DOORS

Entrance and Exit:	Electric type auto door, swing type
Door Open From Outer (Emergency):	Control switch is provided to back of the entrance step panel right side
	Accelerator – inter lock and ning buzzer of door moving
Moving sy	stem is momentary control
	r stops pushing the switch, moving stops in a moment
Emergency Door:	Hinged outward opening swing type
C	Closing type is 2 action lock
Burglar-proof (Rear Eme	ergency Door,
Electrical Control:)	
UNLOCK: The position	n of door starter key is ACC

UNLOCK: The position of door starter key is ACC LOCK: The position of starter key is OFF

STEP WELL

Non-slip checkered steel plate

VENTILATION

1 on front deck for fresh air intake
1 on front door for exhaust

LIGHTING EQUIPMENT


Room Lamps:	3 incandescent lamps of 12W x 2, located over aisle
Step Lamps:	6W located on rear wall of step
Head Lamps:	Quartz halogen-bulb type beam, 2 dual, round type lamp 70W+70W-2/75W-2: white
Front Combination	on Turn signal/hazard
Lamps:	
Front:	21W-2: amber
Side:	10W-2: amber
Clearance:	5W-2: white
Rear Combination	on Lamps Turn signal/hazard
Turn signal/haza	rd: 21W-2: amber
Tail/Stop:	5W-2/21W-2: red
Licence Plate La	mp: 5W-2: white
Back-Up Lamp:	21W-2
Rear-Reflector:	Included in back-up lamp
Side-Reflector:	3 reflectors built on the side skirt

INSTRUMENT


Meter:	Speedometer (electrical)/odometer (LCD)/tachometer/fuel and water temp gauges
Warning Lamp	s: Oil pressure/battery charging/ parking brake/vacuum pressure/front disc brake
Indicator:	Main beam/turn signal/exhaust brake

ROOM COOLER

Model:	FU	SO DIA BUS COOLER BM372
Туре:	Direct d	rive type driven by main engine
Cooling Capacity:		10,800 kcal/h (JIS)



ROSA BE64DJRMUFBD – BODY COLOURS



NOTE: The colours shown are approximate and may differ from the actual colours.

Rosa Bus comes in W48 as standard. P8S, B2E, N9S and F6S are available on special order only.



Transie (

We're proud to be part of the team.

FOR MORE INFORMATION

Mitsubishi FUSO offers a full range of trucks, including the light-duty range of Canters, the medium-duty range of Fighters and the heavy-duty range of Shoguns.

For information on the truck that's right for you, talk to your nearest Mitsubishi FUSO truck dealer.

0800 payload (0800 729 5623) www.fuso.co.nz

